

SHENZHEN TIBTRONIX TECHNOLOGY CO., LTD.



MM OM3 LC-LC duplex

2013/6/1



Shenzhen Tibtronix Technology Co., Ltd.

3/F, 12th Building, Nangang 1st Industrial Park, Baimang Xili, Songbai Road, Nanshan District, Shenzhen, China

Tel: +86 755 23316583

Fax: +86 755 83129773

E-mail: sales@tibtronix.com

<http://www.tibtronix.com>

Specification:

| | |
|-----------------------------------|---|
| Connector | LC Patchcord |
| Type | MM |
| Cable Diameter | 50/125 μ m |
| Insertion loss | Typical insertion loss \leq 0.30dB 0.60dBMax (only APC) |
| Return loss | \geq 50dB |
| Operation Temperature range | -40 $^{\circ}$ C to +80 $^{\circ}$ C |
| End face geometry | Fiber height : 1-3.5 μ m Adjacent fiber height : 0-0.2 μ m Fiber height qty : -0.1 to 0.06 μ m |
| Specialty | <ul style="list-style-type: none">•High precision guided needle design, alignment•ROHS•Precision molding core of MT•UL 94V-0 criterion |
| ANSZ/EIA-455-171 criterion | |



•LC Connector



•LC Connector