

SHENZHEN TIBTRONIX TECHNOLOGY CO., LTD.



MTP/ Male and MTP/ Female OM3 MM

2013/6/1



Shenzhen Tibtronix Technology Co., Ltd.

3/F, 12th Building, Nangang 1st Industrial Park, Baimang Xili, Songbai Road, Nanshan District, Shenzhen, China

Tel: +86 755 23316583

Fax: +86 755 83129773

E-mail: sales@tibtronix.com

<http://www.tibtronix.com>

Specification:

Connector	MTP Patchcord	
Type	SM	MM
Cable Diameter	∅ 0.9mm、∅ 4.6mm	∅ 0.9mm、∅ 4.6mm
Insertion loss	Typical insertion loss≤0.25dB 0.75dBMax (only APC)	Typical insertion loss≤0.20dB 0.60dBMax (only APC)
Return loss	≥60dB (8°C Angle Polish)	≥20dB
Operation Temperature range	-40°C to +60°C	-40°C to +60°C
End face geometry	Fiber height: 1-3.5um Adjacent fiber height: 0-0.2um	Fiber height : 1-3.5um Adjacent fiber height : 0-0.2um Fiber height qty : -0.1 to 0.06um
Specialty	<ul style="list-style-type: none"> •High precision guided needle design, alignment •ROHS •Precision molding core of MT •UL 94V-0 criterion 	
ANSZ/EIA-455-171 criterion		

